



PRESSBAKKER

For 5 og 13 tonns verktøy Utvalgstabell for pressbakker Cu

Til bruk på Cu skjøtehylser i.h.t. DIN 46267 og Cu kabelsko i.h.t. DIN 46235.
Pressbakkene er produsert etter DIN 48083, sekskantpress.

Leder tverrsnitt mm ²	For pressverktøy 5-6 tonn 	El. nr	For pressverktøy 13 tonn 	El. nr
16	MK 8-50	20 198 78	MK 8-C	20 198 66
25	MK 10-50	20 198 79	MK 10-C	20 198 67
35	MK 12-50	20 198 80	MK 12-C	20 198 68
50	MK 14-50	20 198 81	MK 14-C	20 198 69
70	MK 16-50	20 198 82	MK 16-C	20 198 70
95	MK 18-50	20 198 83	MK 18-C	20 198 71
120	MK 20-50	20 198 84	MK 20-C	20 198 72
150	MK 22-50	20 198 85	MK 22-C	20 198 73
185	MK 25-50	20 198 86	MK 25-C	20 198 74
240	MK 28-50	20 198 87	MK 28-C	20 198 75
300			MK 32-C	20 198 76

For C-press klemmer

C-press klemme	5-6 tonns pressbakke	El. nr	Pressbakker 13 tonn	El. nr
25	MC25-50	20 200 90	MC25-C	20 200 93
35	MC35-50	20 200 91	MC35-C	20 200 94
70	MC70-50*	20 200 92	MC70-C	20 200 95
95			MC95-C	20 200 96
185			MC185-C	20 200 97

*Forutsetter glødet leder