

# Wraparound sleeve with aluminum laminate

## Wrap-around sleeve with al.-laminate

Heat-shrink wrap-around sleeve with adhesive and al. laminate, reinforced with polyethylene fibers.

Flexible locking channel in stainless steel. Used for general sealing and protection, repairs of damaged cable or replacement of the outer jacket. Easy installation.

### Abilities:

- High mechanical strength
- Very good moisture barrier
- Broad area of application of different sizes and surfaces
- Shrink Temperature: 120°C
- Good resistance to chemicals
- Max. continuously operating temperature: 95°C
- Can be cut to the desired length before installation



El.no	Title	Inner dia. before shrink mm	Wall thickness fully shrunk mm	Standard length in mm (min)
11 324 76	Wraparound sleeve 43/8-500 Reinforced	43	1.5	500
11 323 54	Wraparound sleeve 52/12-1000 Reinforced	52	1.5	1000
11 323 55	Wraparound sleeve 75/15-1000 Reinforced	75	1.5	1000
11 323 56	Wraparound sleeve 122/30-1000 m/Reinforced	122	1.5	1000
11 323 57	Wraparound sleeve 139/38-1000 Reinforced	138	1.5	1000
11 323 58	Wraparound sleeve 160/42-1000 Reinforced	160	1.5	1000
11 323 59	Wraparound sleeve 210/55-1000 Reinforced	210	1.5	1000