

CONTROL 1 off.

End termination for 1-core medium voltage, Offshore cable

End termination for single-core medium volt cable type RFOU / BFOU, 6 to 36 kV.

Control 1 off. is also used for 3- and 4-core cable when it is combined with the conversion kit from 3- and 4- to 1-core. Complete end-terminations of Control 3 and 4-core cable has it's own catalogsheet.

The Control series in based on heat shrink outer protection and stress-control tubes. Mastic adhesive ensure a good seal against moisture over the cable lugs and outer jacket.

The product has been tested and approved for use up to 24 kV according to Cenelec HD629.2 and IEC 60502.4.

Each set includes 3 complete single-core terminations with assembly instructions. Cable lugs must be ordered separately according to the compression system to be used.

For further information see the installation instruction MB 040.

- Simple installation
- Good cross section flexibility
- Length: 440/480/610 mm



Voltage kV	Cross section mm ²	Title	El. no.
6/10(12)	25-95	Control 1 off 6/10 3x1x25-95	11 316 37
	120-300	Control 1 off 6/10 3x1x120-300	11 316 38
	400-630	Control 1 off 6/10 3x1x400-630	11 323 94
	630-1200	Control 1 off 6/10 3x1x630-1200	11 323 95
8,7/15 12/20(24)	25-95	Control 1 off 12/20 3x1x25-95	11 316 39
	120-300	Control 1 off 12/20 3x1x120-300	11 316 40
18/30(36)	150-300	Control 1 off 18/30 3x1x150-300	11 317 47