

CE off

Shielded end termination for 1-core offshore cable

CE off. is end termination for 1-core cables RFOU / RFOB / BFOU / BFOB 6 / 10 - 12/20 kV. EASG is intended for use on switches, transformers, motors etc. with standard bushings for 250A. The product is supplied in sets of 3 pieces with specially designed copper pin contact manufactured according to DIN 46235 industrial standards. It is important that the pin contact also is pressed with dies that are produced according to this norm. See data sheet for compression dies. For more details on installation see the MB 049.

*** Approved touch proof.**

The product has a outer leading layer that is grounded when mounted.

*** Produced in silicone rubber.**

This provides great flexibility in cross section, optimum insulation qualities and easy installation.

*** Enables outer jacket testing.**

The contact's outer layer is isolated from the cable screen, and should be earthed separately with its own earth movement that follows the set (see photo). This enables measurement of errors (holes) on the outer jacket without having the connector disconnected.

***The product can be installed outdoors and indoors.**

The product has been tested and approved by VDE 0278 and Cenelec HD629.S1.



Art.no	Cross section mm ² Cu		Compressure-system	Title
	6/10 - 8,7/15 kV	12/20 kV		
991355	25	25	Sekskant DIN	CE off. 25S - 2C
991356	35	35	Sekskant DIN	CE off. 35S - 2C
991357	50		Sekskant DIN	CE off. 50S - 2C
991358		50	Sekskant DIN	CE off. 50S - 3C
991359	70	70	Sekskant DIN	CE off. 70S - 3C
991360	95	95	Sekskant DIN	CE off. 95S - 3C

ProCab AS
Kobbervikdalen 61
3036 Drammen, Norway

ProCab as
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00
firmapost@procab.no
www.procab.no

O 508