

CE off

Shielded end termination for 1-core offshore cable

CE off. is end termination for 1-core cables RFOU / RFOB / BFOU / BFOB 6 / 10 - 12/20 kV. EASG is intended for use on switches, transformers, motors etc. with standard bushings for 250A. The product is supplied in sets of 3 pieces with specially designed copper pin contact manufactured according to DIN 46235 industrial standards. It is important that the pin contact also is pressed with dies that are produced according to this norm. See data sheet for compression dies. For more details on installation see the MB 049.

*** Approved touch proof.**

The product has a outer leading layer that is grounded when mounted.

*** Produced in silicone rubber.**

This provides great flexibility in cross section, optimum insulation qualities and easy installation.

*** Enables outer jacket testing.**

The contact's outer layer is isolated from the cable screen, and should be earthed separately with its own earth movement that follows the set (see photo). This enables measurement of errors (holes) on the outer jacket without having the connector disconnected.

***The product can be installed outdoors and indoors.**

The product has been tested and approved by VDE 0278 and Cenelec HD629.S1.



Leading cross section mm ² Cu		Compression- system	Title	El.no
6/10 - 8,7/15 kV	12/20 kV			
25	25	Hexagon DIN	CE off. 25S - 2C	11 315 72
35	35	Hexagon DIN	CE off. 35S - 2C	11 315 73
50		Hexagon DIN	CE off. 50S - 2C	11 315 74
	50	Hexagon DIN	CE off. 50S - 3C	11 315 75
70	70	Hexagon DIN	CE off. 70S - 3C	11 315 76
95	95	Sekskant DIN	CE off. 95S - 3C	11 315 77

ProCab AS
Teglverksveien 97
3057 Solbergelva, Norway

ProCab as
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00
firmapost@procab.no
www.procab.no

O 508