

CC off 1-core

Screened T-connector for 12 and 24 kV 1-core offshore cable no 2.

To be connected to existing T-connector, type CB.

End termination kit adjusted 12-24 kV single-core cable type BFOU, RFOU ect., can be used indoor and outdoor. Using 3-core cable, see table on page O 512. Comes complete with cable lugs from 25 to 300 mm² Cu.

For connection to existing T-connector type CB.

Approved touch-proof (earthed surface).

Material: Silicone rubber (flexible).

Additional products

- Connection of extra cable
- Transitions
- Earthing and measurement
- Surge protection

Approved according to VDE 0278 and Cenelec HD629.S1.



| Art.no | 6/10 kV (12 kV) | 12/20 kV (24kV) | Title 1-core |
|--------|------------------------|------------------------|-------------------------|
| 991361 | 25 mm ² Cu | 25 mm ² Cu | CC off 12/24 3x1x25-2C |
| 991362 | 35 mm ² Cu | 35 mm ² Cu | CC off 12/24 3x1x35-2C |
| 991363 | 50 mm ² Cu | 50 mm ² Cu | CC off 12/24 3x1x50-2C |
| 991364 | 70 mm ² Cu | 70 mm ² Cu | CC off 12/24 3x1x70-2C |
| 991365 | 95 mm ² Cu | 95 mm ² Cu | CC off 12/24 3x1x95-2C |
| 991366 | 120 mm ² Cu | | CC off 12 3x1x120-2C |
| 991367 | | 120 mm ² Cu | CC off 12 3x1x120-3C |
| 991368 | 150 mm ² Cu | 150 mm ² Cu | CC off 24 3x1x150-3C |
| 991369 | 185 mm ² Cu | 185 mm ² Cu | CC off 12/24 3x1x185-3C |
| 991370 | 240 mm ² Cu | 240 mm ² Cu | CC off 12/24 3x1x240-3C |
| 991371 | 300 mm ² Cu | 300 mm ² Cu | CB off 12/24 3x1x300-3C |

*** In the product family there are different additional products**

- Additional contact for extra cable.
- 10 KA touch-safe surge arrester.
- Joint plug.
- Test adapter.
- Earthing adapter.