

CC off 3-leder

Screened T-connector for 12 and 24 kV 3-conductor cable offshore no. 2

Termination set - customized for 12-24 kV 3-core cable type BFOU, RFOU etc. Can be used both indoors and outdoors. Comes complete with cable lugs from 25 to 300 mm² Cu.

For connection to existing T-connector type CB.

Approved Touch-proof (earthed surface).

Material: Silicone Rubber (flexible).

Additional products:

- Connection of additional cable
- Transfers
- Earthing and measurement
- Surge Protection



Approved according to VDE 0278 and Cenelec HD629.S1

6/10 kV (12 kV)	12/20 kV (24kV)	Title 1-core	El.no
25 mm ² Cu	25 mm ² Cu	CC off 12/24 3x25-2C	11 323 60
35 mm ² Cu	35 mm ² Cu	CC off 12/24 3x35-2C	11 323 61
50 mm ² Cu	50 mm ² Cu	CC off 12/24 3x50-2C	11 323 62
70 mm ² Cu	70 mm ² Cu	CC off 12/24 3x70-2C	11 323 63
95 mm ² Cu	95 mm ² Cu	CC off 12/24 3x95-2C	11 323 64
120 mm ² Cu		CC off 12 3x120-2C	11 323 65
	120 mm ² Cu	CC off 24 3x120-3C	11 323 66
150 mm ² Cu	150 mm ² Cu	CC off 12/24 3x150-3C	11 323 67

* The product family includes different optional.

-Additional Help for additional cable.

-10 KA touch safe surge arrester.

-Splice connector.

-Test Adapter.

-Earthing Adapter.