

# CE

## Screened angle connector to 12 and 24 kV cable

Intended for connection of switches, transformers, motors etc. with standard 250A bushings. The product comes complete with a specially designed Al-copper lug. **It is important that you choose the right set, according to the compression dies system to be used when ordering.** See table below. For further information see the installation description 109 MB.

**\* *Approved touch-proof.***

The product has a outer leading layer that is earthed when mounted.

**\* *Produced in silicone rubber.***

This provides great flexibility in cross section, optimum insulation qualities and easy installation.

**\* *Enables outer jacket testing.***

The contact's outer layer is isolated from the cable screen, and should be earthed separately with its own earth movement that follows the set (see photo). This enables measurement of errors (holes) on the outer jacket without having the connector disconnected.

**\* *The product can be installed outdoors and indoors.***

The product is tested and approved to VDE 0278 and Cenelec HD629.S1.



El.no	Title	Compressure system	Cross section mm <sup>2</sup>	
			12 kV	24 kV
11 315 78	CE 24/250 25S - 3	Hexagon DIN		25 Al
11 315 79	CE 24/250 25C - 3	Hexagon DIN		25 Cu
11 315 80	CE 12/24/250 50S - 3	Hexagon DIN	50 Al	50 Al
11 315 81	CE12/ 24/250 50D - 3	Deep - compression	50 Al	50 Al
11 315 82	CE 12/24/250 95S - 3	Hexagon DIN	95 Al	95 Al
11 315 83	CE12/ 24/250 95D - 3	Deep - compression	95 Al	95 Al
11 316 17	CE 12/24/250 25-95 - 3	Screw Al/Cu	25-95	25-95
11 316 60	Conversion kit OS from 3-core cable for CC/CB			

ProCab AS  
Teglverksveien 97  
3057 Solbergelva, Norway

**ProCab as**  
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00  
firmapost@procab.no  
www.procab.no