

# PETROLINK 12-24-36 kV

Cable joints for cable type  
TSLP/TFLP 12-24-36 kV



Petrolink cable joints are custom cables used on process plants. The cables is typically referred to as TFLP / TSLP with a middle jacket of polyamide laminated Al foil, this provides protection against possible oil products in soil.

12/24/36 kV joints are constructed the same way as cables and tested to the same requirements. They have a special protection against ingress of moisture and harmful oil products.

Test report provided on request.

ProCab AS  
Kobbervikdalen 61  
3036 Drammen, Norway

**ProCab as**  
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00  
firmapost@procab.no  
www.procab.no

# PETROLINK 12-24-36 kV

Table

Cross section mm <sup>2</sup>	Title	El.no
12 - 24 kV 1-leder		
1 x 25-50	Petrolink 12-24 kV 1 x 25-50	991458
1 x 70-240	Petrolink 12-24 kV 1 x 70-240	991427
12 - 24 kV 3-leder		
3 x 25-50	Petrolink 12-24 kV 3 x 25-50	991403
3 x 70-240	Petrolink 12-24 kV 3 x 70-240	991404
36 kV 1-leder		
1 x 70-240	Petrolink 36 kV 1 x 70-240	991406
1 x 185-500	Petrolink 36 kV 1 x 185-500	991460
1 x 400-800	Petrolink 36 kV 1 x 400-800	991414
36 kV 3-leder		
3 x 35-95	Petrolink 36 kV 3 x 35-95	991415
3 x 70-240	Petrolink 36 kV 3 x 70-240	991416