

CB 36

Screened T-connector for 12, 24 and 36 kV cables with compressure cable lugs Al

Used for connection to standardized 630 A bushings type C, ref. EN 50180, DIN 47636 on switches, transformers and motors. The product comes complete in a set of three pieces. with specially constructed lugs. For further information see the installation description MB 117 and 118.

* **Approved touch-proof.** The product has a outer conductive layer that is grounded when mounted.

* **Made of flexible silicone rubber.** This provides great flexibility in cross section, optimum insulation properties and easy installation.

* **The connector allows outer jacket testing.** The cable screen is isolated from earth without disconnecting the T-connector. This is because the T-contacts outer conductive layer has a separate ground connection that easily can be separated from the cable screen.

To order contact to 630 A bushings, see table below.

* **The product is tested and approved according to VDE 0278 and Cenelec HD629.1.**



El. no	Title: T-connector	Compressure- system	Cross section mm ² Al		
			12 kV	24 kV	36 kV
11 320 02	CB 36-630 50S	Hexagon DIN			50
11 320 03	CB 36-630 50D	Deep-compression			50
11 320 04	CB 36-630 95S	Hexagon DIN			95
11 320 05	CB 36-630 95D	Deep-compression			95
11 320 06	CB 36-630 150S	Hexagon DIN			150
11 320 07	CB 36-630 150D	Deep-compression			150
11 320 08	CB 36-630 240S	Hexagon DIN			240
11 320 09	CB 36-630 240D	Deep-Compression			240
11 320 10	CB 36-1250 400S	Hexagon DIN	400		
11 320 12	CB 36-1250 630S	Hexagon DIN	630		
11 320 13	CB 36-1250 400S	HexagonDIN		400	400
11 320 14	CB 36-1250 630S	Hexagon DIN		630	630