

CB 36 with mechanical lug

Screened T-connector for 12, 24 and 36 kV cables

Used for connection to standardized 630 A bushings type C, ref. EN 50180, DIN 47636 on switches, transformers and motors. The product comes complete in a set of three pieces. with specially constructed lugs. For further information see the installation description MB 117 and 118.

* **Approved touch-proof.** The product has a outer conductive layer that is earthed when mounted.

* **Made of flexible silicone rubber.** This provides great flexibility in cross section, optimum insulation properties and easy installation.

* **The connector allows outer jacket testing.** The cable screen is isolated from earth without disconnecting the T-connector. This is because the T-contacts outer conductive layer has a separate ground connection that easily can be separated from the cable screen.

To order contact to 630 A bushings, see table below.

* **The product is tested and approved according to VDE 0278 and Cenelec HD629.1.**



El. no	Title: T-connector	Cable lug system	Cross section mm ² Al/Cu		
			12 kV	24 kV	36 kV
11 321 14	CB 36-630 50-95	Skrew Al/Cu			50-95
11 321 15	CB 36-630 150-240	Skrew Al/Cu			150-240
11 321 16	CB 36-630 400	Skrew Al	400	400	
11 320 11	CB 36-630 400	Skrew Al/Cu			400
11 321 17	CB 36-1250 400-630	Skrew AL/Cu	630	400	400
11 321 18	CB 36-1250 630	Skrew Al/Cu		630	630