

CB 36 with mechanical lug

Screened T-connector for 12, 24 and 36 kV cables

Used for connection to standardized 630 A bushings type C, ref. EN 50180, DIN 47636 on switches, transformers and motors. The product comes complete in a set of three pieces. with specially constructed lugs. For further information see the installation description MB 117 and 118.

* **Approved touch-proof.** The product has a outer conductive layer that is earthed when mounted.

* **Made of flexible silicone rubber.** This provides great flexibility in cross section, optimum insulation properties and easy installation.

* **The connector allows outer jacket testing.** The cable screen is isolated from earth without disconnecting the T-connector. This is because the T-contacts outer conductive layer has a separate ground connection that easily can be separated from the cable screen.

To order contact to 630 A bushings, see table below.

* **The product is tested and approved according to VDE 0278 and Cenelec HD629.1.**



| El. no | Title: T-connector | Cable lug system | Cross section mm ² Al/Cu | | |
|-----------|-----------------------|---------------------|-------------------------------------|-------|---------|
| | | | 12 kV | 24 kV | 36 kV |
| 11 321 14 | CB 36-630 50-95 | Skrew Al/Cu | | | 50-95 |
| 11 321 15 | CB 36-630 150-240 | Skrew Al/Cu | | | 150-240 |
| 11 321 16 | CB 36-630 400 | Skrew Al | 400 | 400 | |
| 11 320 09 | CB 36-630 400 | Skrew Al/Cu | | | 400 |
| 11 321 17 | CB 36-1250 400-630 | Skrew AL/Cu | 630 | 400 | 400 |
| 11 321 18 | CB 36-1250 630 | Skrew Al/Cu | | 630 | 630 |