

# CC 36 with mechanical lug

For connection of cable nr. 2, to existing T-connector of the type CB 36, produced by NKT-cables

CC is end terminations at 12, 24 and 36 kV cable, which already has a cable connected using the T-connector type CB 36. The product comes complete in a set of three pieces, with specially constructed lugs. When ordering, it is therefore important to choose the right product acc. to the compression system to be used. See table below. For further information see the installation description MB 126 and MB 127

\* **Approved touch-proof.** The product has a outer conductive layer that is earthed when mounted.

\* **Made of flexible silicone rubber.** This provides great flexibility in cross section, optimum insulation properties and easy installation.

\* **The connector allows outer jacket testing.** The cable screen is isolated from earth without disconnecting the T-connector. This is because the T-contacts outer conductive layer has a separate ground connection that easily can be separated from the cable screen.

\* **The product is tested and approved according to VDE 0278 and Cenelec HD629.1.**



El. no	Title: T-connector	Cable-lug type	Cross section mm <sup>2</sup> Al		
			12 kV	24 kV	36 kV
11 321 19	CC 36-630 50-95	Screw Al/Cu			50-95
11 321 20	CC 36-630 150-240	Screw Al/Cu			150-240
11 321 21	CC 36-630 400	Screw Al	400	400	400
11 321 22	CC 36-1250 400-630	Screw AL/Cu	630	400	400
11 321 23	CC 36-1250 630	Screw Al/Cu		630	630