

# LINK with mechanical ferrules

Splicing tubes of shrink plastic for 1 kV,  
plastic and paper insulated cable

Shrink plastic consists of polyolefin with adhesive on the inside surface. The joint kits have mechanical ferrules for conductor joint supplied. The joint program consists of seven series: Flamelink, Link, Link+, Logilink, Link Trans og Link Paper.

See table to find suitable joint-house.

- **Flamelink** : Mechanical ferrules, phase tubes, outer tube and medium tubes.
- **Link** : Mechanical ferrules, phase tubes and outer tubes.
- **Link+** : Mechanical ferrules, phase tubes, medium tubes og outer tubes.
- **Logilink** : Mechanical ferrules, phase tubes, mesh og outer tube.
- **Link Trans** : Mechanical ferrules, phase tubes, insulation tube, Cu-braid and outer tubes.
- **Link Paper** : Mechanical ferrules, phase tubes, two insulation tubes, Cu-braid and outer tubes.



El.no	Title	Cross-sectional area mm <sup>2</sup>
<b>Flamelink 5 S. For 5-core plastic insulated cabel. Joint with medium jacket</b>		
11 324 90	Flamelink Prolight	5x25 Al
11 324 91	Flamelink Prolight	5x50/95 Al
<b>Link 4 S. For 4-core plastic insulated cable. No medium jacket</b>		
11 319 59	Link Veilys 4 S 4x16-25	16-25
11 319 60	Link 4 S 4x25-95	25-95
11 319 61	Link 4 S 4x95-240	95-240
<b>Link 4+ S. For 4-core plastic insulated cabel. Joint with medium jacket</b>		
11 319 62	Link 4+ S 4x25-95	25-95
11 319 63	Link 4+ S 4x95-240	95-240
<b>Logilink S. For 3 and 4-core plastic insulated cabel with and without screen</b>		
11 319 64	Logilink1 S 3-4x25-95	20-95
11 319 65	Logilink2 S 3-4x95-240	95-240
<b>Link3+. For 3-core plastic insulated cabel with shield. Joint with medium jacket</b>		
11 319 68	Link3+ 3x25-95	25-95
11 319 69	Link3+ 3x95-240	95-240
<b>Link trans S. For plastic insulated cabel against paper insulated cabel</b>		
11 319 70	Link T S 3x25-95	25-95
11 319 71	Link T S 3x95-240	95-240
<b>Link papir S. For paper insulated cabel against paper insulated cabel</b>		
11 319 72	Link P S 3x25-95	25-95
11 319 73	Link P S 3x95-240	95-240