

# CB single core

## Screened termination for 1-core shipping cable type TFOI / MPRXCX

CB is terminations on 6/10 - 12/20 kV cable for connection to standardized 630A bushings.

The product is delivered complete in sets of three pieces, with specially designed lugs produced after DIN 46235 industry standard. It is important that the cable lug is pressed with slopes that are manufactured to the same standard. See data sheet for pressure slopes. For more details on mounting see MB 412.

### **Approved safe to touch.**

The product has an outer conductive which is grounded upon installation.

**Made of** flame retardant silicone rubber (self-extinguishing).

**Special features:** The cable Cu-screen can be easily separated for testing the outer sheath.



| El.no.    | Title single core     | 6/10 kV<br>(12 kV)     | 12/20 kV<br>(24kV)     |
|-----------|-----------------------|------------------------|------------------------|
| 11 322 09 | CB-B 12/24 3x1x25-2C  | 25 mm <sup>2</sup> Cu  | 25 mm <sup>2</sup> Cu  |
| 11 322 10 | CB-B 12/24 3x1x35-2C  | 35 mm <sup>2</sup> Cu  | 35 mm <sup>2</sup> Cu  |
| 11 322 11 | CB-B 12/24 3x1x50-2C  | 50 mm <sup>2</sup> Cu  | 50 mm <sup>2</sup> Cu  |
| 11 322 12 | CB-B 12/24 3x1x70-2C  | 70 mm <sup>2</sup> Cu  | 70 mm <sup>2</sup> Cu  |
| 11 323 10 | CB-B 24 3x1x95-3C     | 95 mm <sup>2</sup> Cu  | 95 mm <sup>2</sup> Cu  |
|           | CB-B 12 3x1x120-2C    | 120 mm <sup>2</sup> Cu |                        |
| 11 322 14 | CB-B 12 3x1x120-3C    |                        | 120 mm <sup>2</sup> Cu |
| 11 322 15 | CB-B 24 3x1x150-3C    | 150 mm <sup>2</sup> Cu | 150 mm <sup>2</sup> Cu |
| 11 322 16 | CB-B 12/24 3x1x185-3C | 185 mm <sup>2</sup> Cu | 185 mm <sup>2</sup> Cu |
| 11 323 11 | CB-B 12/24 3x1x240-3C | 240 mm <sup>2</sup> Cu | 240 mm <sup>2</sup> Cu |
| 11 323 12 | CB-B 12/24 3x1x300-3C | 300 mm <sup>2</sup> Cu | 300 mm <sup>2</sup> Cu |