

# CB 3-core

Screened connector for 3-core shipping cable, type TFOI / MPRXCX

**Termination kit** suited for 3-core, type TXOI or MPRXCX the like 6/10 or 12/20 kV.

**For connection** against standardized bushings.

**Delivered** complete with cable lugs from 25-300 mm<sup>2</sup> Cu

**Approved finger protection** (Grounded surface)

**Material:** Flame retardant silicone rubber (self-extinguishing)

Program of additional products

- Additional plug cable no. 2 (CC-contact)
- Transfers from 250A-630A
- Grounding etc.
- Surge Protection

**Approved by:** VDE 0278 and Cenelec HD629.S1



El.no.	Title 3-core	6/10 kV (12 kV)	12/20 kV (24 kV)
11 322 88	CB-B 12/24 3x25-2C	25 mm <sup>2</sup> Cu	25 mm <sup>2</sup> Cu
11 322 89	CB-B 12/24 3x35-2C	35 mm <sup>2</sup> Cu	35 mm <sup>2</sup> Cu
11 322 90	CB-B 12/24 3x50-2C	50 mm <sup>2</sup> Cu	50 mm <sup>2</sup> Cu
11 322 91	CB-B 12/24 3x70-2C	70 mm <sup>2</sup> Cu	70 mm <sup>2</sup> Cu
11 322 93	CB-B 12 3x95-2C	95 mm <sup>2</sup> Cu	95 mm <sup>2</sup> Cu
11 322 94	CB-B 12 3x120-2C	120 mm <sup>2</sup> Cu	
	CB-B 24 3x120-3C		120 mm <sup>2</sup> Cu
11 322 95	CB-B 24 3x150-3C	150 mm <sup>2</sup> Cu	150 mm <sup>2</sup> Cu
11 322 97	CB-B 24 3x240-3C	240 mm <sup>2</sup> Cu	