

VULCAN QUADROFOIL - VRQ

Cable cleats for quadrofoil cable where moderate levels of short circuit withstand are required

Qualifications :

Tested at the British Short-Circuit Testing Station.

Approved for 43 kA RMS and 93,6 kA Peak.

Short circuit: 0,3 sek

Fixing distance: 300 mm


Test report can be provided upon request.

Materials : 316 Stainless steel.

Liner of 0-halogen LSF plastic.

To select: Find your single cable diameter, then find the title and El.no. As the table shows, each cleat are range taking, if doubt, pick the larger size.

Example: For use on 4x1-core cable with diametres 44 mm, order VRQ-05.



El.no	Title	Cable diameter (4x)		Dimension			
		Min dia. mm	Max dia. mm	W(max) mm	H(max) mm	D mm	Weight g
13 181 33	VRQ-01	23	25	68	110	10,2	284
13 181 34	VRQ-02	26	27	70	113	10,2	286
13 181 35	VRQ-03	28	32	80	128	10,2	318
13 181 36	VRQ-04	33	42	103	148	10,2	378
13 181 37	VRQ-05	43	47	120	165	10,2	452
13 181 38	VRQ-06	48	50	121	170	10,2	467
13 181 39	VRQ-07	51	57	140	190	10,2	486
13 181 40	VRQ-08	58	63	150	200	10,2	499
13 181 41	VRQ-09	64	70	170	218	10,2	581