

PLASTIC CABLECLEAT - 2F+

Cableclamp produced in LSF plastic for single and 3-core cable

Cable cleat produced in black, self-extinguishing and UV stabilized nylon LSF. The cleat is halogen free.

The cleats is supplied without liner and anchor bolts / nuts. Procab do no have this in stock, so it must be purchased separately. The cleat is tested to withstand up to 76 kA with a fixing distance of 600mm between each staple.

The cleat is used for fixing the single cables or round multi-conductor cables.



El.no	Title	Kabel dia. mm	W mm	H mm	D mm	P mm	Bolts
13 182 49	2F+-07LSF	38-46	92	60	54	68	2xM10
13 182 38	2F+-08LSF	46-51	103	71	54	79	
13 182 39	2F+-09LSF	51-57	103	76	54	79	
13 182 40	2F+-10LSF	57-64	103	82	54	79	
13 182 41	2F+-11LSF	64-70	130	89	54	106	
13 182 42	2F+-1200LSF	70-76	128	95	75	104	2xM12
13 182 43	2F+-1201LSF	76-83	135	100	75	111	
13 182 44	2F+-1202LSF	83-90	143	108	75	119	
13 182 45	2F+-131LSF	90-97	165	115	100	138	
13 182 46	2F+-132LSF	97-105	171	122	100	144	
13 182 47	2F+-141LSF	105-112	178	130	100	151	
13 182 48	2F+-142LSF	112-120	187	138	125	160	
13 182 50	2F+-151LSF	120-128	196	148	125	168	
13 182 51	2F+-152LSF	128-135	203	158	125	176	

