

# BAND-FAST

## Plastic coated cable ties in stainless steel

### Features:

- Low profile finish
- Stainless steel 316 (0,4mm band tickness)
- PPA 571 coating (0,4mm coating tickness)
- Zero halogen, low smoke and fume.
- DNV og Germanischer Lloyd type approved materials.
- Captive sealing clip, when use of recommended band-fast tool, C075.
- Handles various cable sizes very well
- Standard width 5/8 "(15.88 mm.) - Other sizes available.
- Fully rounded edges, also on the end of the band.
- Low weight
- No accesserioes required (fixing, liners, packers, studding etc.)
- Standard colour: Black. (Other colours available upon request)



### Short-circuit-tested by SINTEF.

El.no	Title	Single or double wrap	Lenght mm	*Max cable dia. (single cable config.) (mm)	*Max cable dia. (Trefoil cable config.) (mm)	*Max cable dia. (Quadrafoil cable config.) (mm)	Weight (kg)
13 183 21	LFAC-F1015M030-A900	Single	300	40	13	12	0,025
13 183 22	LFAC-F1015M040-A900	Single	400	75	28	25	0,030
13 183 23	LFAC-F1015M050-A900	Single	500	100	43	37	0,038
13 183 24	LFAC-F1015M060-A900	Single	600	130	57	50	0,045
13 183 25	LFAC-F1015M070-A900	Single	700	160	70	60	0,052
13 183 26	LFFC-F1015M030-A900	Double	300	25	10	9	0,025
13 183 27	LFFC-F1015M040-A900	Double	400	40	13	12	0,030
13 183 28	LFFC-F1015M050-A900	Double	500	55	21	18	0,038
13 183 30	LFFC-F1015M060-A900	Double	600	70	28	25	0,045
13 183 31	LFFC-F1015M070-A900	Double	700	85	35	31	0,052
13 183 32	LFFC-F1015M080-A900	Double	800	100	42	37	0,060
13 183 33	LFFC-F1015M100-A900	Double	1000	130	57	50	0,075
13 183 29	Tensioning tool for Band-Fast C075						1,040

**Delivered in packages of 100 pieces.**

\* Note: Maximum cable dia. is only a recommendation. Please note that **ladder pin dia.** comes in addition.