

FCFW

Thick wall heat shrink tube, self extinguishing,
with adhesive

- Very good mechanical strength
- Flame retarded
- Do not crack when it is overheated
- Mechanical strength of ISO 527 to 1.2: 350% at break
- Shrink ratio 3:1
- Good insulation: 20kV/mm
- Color: Black



El.no	Title	Inner dia. before shrink mm	Inner dia. fully shrunk mm	Wall thick- ness fully shrunk mm	Standard length in mm
18 189 86	FCFW 9/3	9,0	3,0	2,0	1000
18 189 87	FCFW 13/4	13,0	4,0	2,5	1000
18 189 88	FCFW 19/6	19,0	6,0	3,0	1000
18 189 89	FCFW 28/9	28,0	9,0	3,0	1000
18 189 90	FCFW 38/12	38,0	12,0	3,5	1000
18 189 91	FCFW 51/16	51,0	16,0	3,5	1000
18 189 92	FCFW 68/22	68,0	22,0	4,0	1000
18 189 93	FCFW 90/30	90,0	30,0	4,0	1000
18 189 94	FCFW 120/40	120,2	40,0	4,5	1000

ProCab AS
Teglverksveien 97
3057 Solbergelva, Norway

ProCab as
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00
firmapost@procab.no
www.procab.no