

# Nexans GT2 FR

Heatshrink tube, 0-Halogen,  
Flame retardant

Heatshrink tubes for joints and terminations up to 52 kV. Well suited for both indoor and outdoor use.

GT2 FR is flame retardant and halogen free, which makes it suitable together with similar characteristics. GT2 FR is delivered without glue, if need of sealing, use red mastic supplied separately, el.no: 18190 99.

- Material: Shrink plastic in polyolefin
- Shrink temp .: 125 ° C
- Continuous operating temperature from -40 ° C to 135 ° C
- Flame retardant
- 0-Halogen
- Max. voltage: 52 kV
- Color: Red



El.no.	Title	Diameter Before shrink/ after (mm)	Thickness fully shrunk (mm)	Meter per roll
18 191 83	GT2-20 FR	23/8	1,4	40
18 191 84	GT2-30 FR	34/10	2,5	40
18 191 85	GT2-35 FR	39/12	2,8	40
18 191 86	GT2-40 FR	48/19	2,9	30
18 191 87	GT2-50 FR	59/24	3,0	20
18 191 88	GT2-60 FR	65/29	3,1	20
18 191 89	GT2-70 FR	80/38	3,2	20
18 191 90	GT2-100 FR	120/50	3,8	20
18 191 91	GT2-130 FR	130/50	4,0	20