

LINK

Splices of shrink plastic for 1 kV, plastic and paper insulated cable

In order to determine what the different splice types is suited for, see the table below.

The splice program comprise five series with following content:

Link: Ferrules insulation, outer jacket, optionally Cu-mesh for 3-core.

Link+: Ferrules insulation, outer jacket, medium ferrules and optionally Cu-mesh.

Logilink: Ferrules insulation, Cu-mesh and outer jacket.

Link Trans : Ferrules insulation, transition splice, cable breakout, Cu-mesh, spring clamp and outer jacket (transition plastic and paper insulated cabel)

Link Papir: Ferrules insulation, transition splice, 2 shrink terminations, Cu-mesh, Cu-braid, 2 spring clamps and outer jacket.

Link Multicore: Ferrules insulation, Cu-mesh and outer jacket.



El.nr	Benevnelse	Tverrsnittsområde mm ²
Link 4. For 4-conductor plastic insulated cable. No medium jacket		
11 315 00	Link4 4x1,5-6	1,5-6
11 315 01	Link4 4x6-16	6-16
11 315 02	Link4 4x16-50	16-50
11315 03	Link4 4x25-95	25-95
11 315 04	Link4 4x95-150	95-150
11 315 05	Link4 4x150-300	150-300
Link 4. For 4-conductor plastic insulated cabel. The joint has a medium jacket		
11 315 06	Link4+ 4x1,5-6	1,5-6
11 315 07	Link4+ 4x6-16	6-16
11 315 08	Link4+ 4x16-50	16-50
11 315 09	Link4+ 4x25-95	25-95
11 315 10	Link4+ 4x95-150	95-150
11 315 11	Link4+ 4x150-300	150-300
Logilink. For all types of plastic insulated cable		
11 315 12	Logilink1 3-4x10-95	10-95
11 315 13	Logilink2 3-4x95-240	95-240
Link3+. For 3-core plastic insulated cable with screen. The splice has a medium jacket		
11 315 23	Link3+ 3x6-16	6-16
11 315 24	Link3+ 3x16-25	16-25
11 315 25	Link3+ 3x25-95	25-95
11 315 26	Link3+ 3x95-150	95-150
11 315 27	Link3+ 3x150-240	150-240
Link trans. For plastic insulated cable against paper insulated cable		
11 315 28	Link T 3x16-50	16-50
11 315 29	Link T 3x50-150	50-150
11 315 30	Link T 3x150-240	150-240
11 318 02	Link T 3x120-4x240	120-240
Link paper. For paper insulated cable against paper insulated cable		
11 315 14	Link P 3x16-50	16-50
11 315 15	Link P 3x50-95	50-95
11 315 16	Link P 3x120-240	120-240
Link Multicore. For plastic insulated cable		
11 323 68	Link M 0,6-1kV 7x1,5-2,5	1,5-2,5
11 323 69	Link M 0,6-1kV 12x1,5-2,5	1,5-2,5
11 323 70	Link M 0,6-1kV 27x1,5-2,5	1,5-2,5
11 324 32	Link M 0,6-1kV 37x1,5-2,5	1,5-2,5