MONO i

Termination for single and 3-core medium voltage cable (indoor)

Termination for single and 3-core medium voltage cable, type 24 kV MONOi, TSLP-cable.

Termination MONOi, consist of one heatshrink-tube containing both field distributor and insulation, in one operation.

MONOi-series is based on heatshrink-plastic used for protection against creepage and field distribution. Mastic ensure good sealing both on lugs and outer jacket. An additional set ensures grounding aliminium-laminate and connect it together with the Cu-screen.

The product is tested and approved for use up to 24kV after norm Cenelec HD 629.152 og IEC 60502-4.

Each kit contains 3 complete single core leder terminations with installation instructions. Lugs must be ordered separately according to used crimp-system. For further information, see installation instruction

For further information, see installation instruction MB 1033 (english version).

- Easy installation
- Good cross-section flexibility
- Length: 320*/340/370 mm



Single core

Art.no	Cross-section mm ²	Title	Voltage kV
991440*	25-95	Ende VK MONOi HC 3x1x25-95	
991441*	120-240	Ende VK MONOi HC 3x1x120-240	24kV
991442	185-400	Ende VK MONOi HC 3x1x185-400	24KV
991443	400-630	Ende VK MONOi HC 3x1x400-630	

3-core

Art.no	Cross-section mm ²	Title	Voltage kV
991444	25-95	Ende VK MONOi HC 3x25-95	- 24kV
991445	120-240	Ende VK MONOi HC 3x120-240	

ProCab AS Kobbervikdalen 61 3036 Drammen, Norway



P 500

Tel: +47 32 23 77 00 firmapost@procab.no www.procab.no