

FIRELINK 0,6/1

Fire resistant cable joint for power cable
BFXI 0,6/1 kV, cable without screen



Cable jointing concept based on 0-halogen heatshrinkable tubings.

The concept is tested and approved in accordance with IEC 60333-1 and NEK 606. After 90 minutes in 830 °C the cable joints inner jacket and ferrule insulation are without damages. See picture. Pressure tested against wateringress up to 6,5 bar. Tested on Sintef, 2016.

Test report on request.

Easy and quick installation. Small diameter increase over joint compared to cable diameter.

The cable joint will fit cables of type BFXI, 0,6/1 kV and contains everything needed for the job included ferrules and installation instruction (English and Norwegian).



SELECTION TABLE AND PRODUCT NO, SEE NEXT PAGE.

ProCab AS
Kobbervikdalen 61
3036 Drammen, Norway

ProCab as
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00
firmapost@procab.no
www.procab.no

SELECTION TABLE

for Firelink 0,6/1 (BFXI) fire resistant cable joint,
fits BFXI 0,6/1 kV, without screen

Cable size mm ²	Title	El.no
3x1,5	FIRELINK 0,6/1-2/4x1,5-2,5	11 321 73
3x2,5	FIRELINK 0,6/1-2/4x1,5-2,5	11 321 73
3x4	FIRELINK 0,6/1-3/4x4-6	11 321 74
3x6	FIRELINK 0,6/1-3/4x4-6	11 321 74
3x10	FIRELINK 0,6/1-3/4x10-16	11 321 75
3x16	FIRELINK 0,6/1-3/4x10-16	11 321 75
5x4	FIRELINK 0,6/1-5x4-6	11 321 76
5x6	FIRELINK 0,6/1-5x4-6	11 321 76
5x10	FIRELINK 0,6/1-5x10-16	11 321 80
5x16	FIRELINK 0,6/1-5x10-16	11 321 80
5x25	FIRELINK 0,6-1-5x25/35	11 325 79
5x35	FIRELINK 0,6-1-5x25/35	11 325 79

For other cable sizes than those listed here, contact

ProCab AS Tel: +47 32 23 77 00.

We have splices for all sizes.