

# CONTROL 3 and 4 off.

Cable termination for 3- and 4-core medium voltage cable, Offshore.

End termination for 3- and 4-core medium volt cable for the type RFOU/BFOU 6 - 24 kV.

The control series is based on heat shrink outer protection and stress control tubes. Mastic adhesive ensure a good seal against moisture over the cable lugs and the outer jacket.

Products are tested and approved for use up to 24 kV for Cenelec HD629.2 and IEC 60502.4.

Each kit contains a complete 3-core termination phase-length 3 x 0.7 m. For request for longer phase length, this must be specified when ordering.

Cable lugs must be ordered separately according to the compression system to be used.

- Easy installation.
- Good cross section flexibility



## For 3-core

Voltage kV	Cross section mm <sup>2</sup>	Title	El.no.
6/10	25-95	Control 3 off 12A 3 x 25-95	11 315 91
	120-300	Control 3 off 12A 3 x 120-300	11 315 92
8,7/15 12/20	25-95	Control 3 off 24A 3 x 25-95	11 315 93
	120-300	Control 3 off 24A 3 x 120-300	11 315 94

## For 4-core

Voltage kV	Cross section mm <sup>2</sup>	Title	El.no.
6/10	25-95	Control 4 off 12A 4 x 25-95	11 315 95
	120-300	Control 4 off 12A 4 x 120-300	11 315 96
8,7/15 12/20	25-95	Control 4 off 24A 4 x 25-95	11 315 97
	120-300	Control 4 off 24A 4 x 120-300	11 315 98