

# FIRELINK 12

Fire resistant cable splice for M.V power cables  
RFOU-FR 6/10(12) kV




## Description

Cable splicing concept based on flame retardant, Zero-halogen heat-shrinkable tubing. Favuseal as fire protection.

”Powered by FAVUSEAL™”

## Qualifications

The concept is tested and approved in acc. with:  
IEC 60332-1 (Flame retardant, 750°C/120min.)  
IEC 61034-1 (Low smoke)  
HD629-1:2014 (Electrical type approval)



*Test reports on request.*

## Special features

- Quick and easy installation
- Slim and limited diameter increase
- Each kit cover several cross-sections



Ferrules must be ordered separately.

For selection table and product number, see next page.

ProCab AS  
Teglverksveien 97  
3057 Solbergelva, Norway

**ProCab as**  
PRODUKTER FOR KABEL

Tel: +47 32 23 77 00  
firmapost@procab.no  
www.procab.no

# SELECTION TABLE

Firelink 12 kV

## Single core

Voltage kV	Cross section range mm <sup>2</sup>	Product name	Product no.
6/10 (12)	25 - 95	FIRELINK 6-20 - 1x25-95	11 316 61
	120 - 300	FIRELINK 6-20 - 1x120-300	11 316 62