

# SIEVERT GAS BURNER SET

## Sievert Promatic reinforced handle




- Plastic composite handle reinforced with 30% glass fibres for maximum durability
- Double moulded soft grip for highest comfort and usability
- Piezo ignitor with instant trigger on/off function
- Bayonet fitting for burners
- Swivelling hose connection to avoid hose drag
- Combined suspension hook and footstand
- Valve for precise flame setting

## Promatic burners - Heatshrink



- Soft flame design ideal for cable work and other heat shrinking applications
- Soft flame burners with sweeping, powerful yellow and blue soot-free windproof flames
- Fresh air sucks in and keeps the burner head cold to minimize the risk of burning the shrink material
- To heat the sleeves efficiently but still soft enough not to overheat the shrink material
- Working pressure 2 bar



| Soft flame burners   |      |      |
|--|------|------|
| Burner diameter Ø mm   | 38   | 50   |
| Gas Consumption, g/h at 2 bar                                    | 900  | 2000 |
| Effect, kW   | 11,5 | 26   |
| For thick walled sleeves max, mm<br>Also for thin walled sleeves | 150  | 150  |



| Art.no   | Sievert gas burner set  |
|----------|---|
| 99 10 44 | 1 pc. Handle Sievert Promatic<br>1 pc. Soft flame burner Ø38mm<br>1 pc. Soft flame burner Ø50mm<br>1 pc. Propane hose 6,3mm 3m<br>1 pc. Regulator 2 bar<br>1 pc. Powercase suitcase |

